

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 07-017222
(43)Date of publication of application : 20.01.1995

(51)Int. CI. B60C 17/04


(21)Application number : 05-165506 (71)Applicant : BRIDGESTONE CORP
(22)Date of filing : 05.07.1993 (72)Inventor : TAKAYAMA MASAHIRO
WADA MITSUISA

(54) CORE ASSEMBLY BODY FOR PNEUMATIC TIRE

(57)Abstract:

PURPOSE: To provide a pneumatic tire core assembly body which can reduce noise without causing the unbalance of the tire itself by arranging properly a resonance impeding material to damp a cavity resonance sound to be generated by air vibration in a tire cavity.

CONSTITUTION: A pneumatic tire core assembly body 4 is arranged on the well 3 of a rim 2, and is furnished with a tire inside resonance impeding material 5 consisting of porous substance or fiberlike substance whose apparent density is not more than 0.1g/cm³.



LEGAL STATUS

[Date of request for examination] 07.06.2000

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number] 3373596

[Date of registration] 22.11.2002

[Number of appeal against examiner's

decision of rejection]

[Date of requesting appeal against
examiner's decision of rejection]

[Date of extinction of right]

Copyright (C); 1998, 2003 Japan Patent Office